

Specifications

| | |
|-------------------------|--|
| CPU | AMD CPU on Board ;Fusion APU E-350 Dual-Core Processors |
| Chipset | AMD® FCH A50 (Hudson M1) |
| Memory | 2 x DIMM, Max. 8 GB, DDR3 1066/800 Non-ECC,Un-buffered Memory * Please refer to www.asus.com or user manual for Memory QVL. * When installing total memory of 4GB capacity or more, Windows 32-bit operation system may only recognize less than 3GB. Hence, a total installed memory of less than 3GB is recommended. |
| Expansion Slots | 1 x PCIe 2.0 x16 (at x4 mode, with latch) Integrated AMD® Radeon HD 6310 |
| VGA | Supports DVI with max. resolution up to 1920x1200@60Hz Supports HDMI with max. resolution up to 1920x1080@60Hz |
| Storage | Southbridge 5 xSATA 6.0 Gb/s ports 1 xExternal SATA 6Gb/s |
| LAN | Realtek® 8111E PCIe Gigabit LAN controller ALC892 8-Channel High Definition Audio CODEC |
| Audio | Supports DTS Surround Sensation Ultra-PC * Use a chassis with HD audio module in the front panel to support an 8-channel audio output. |
| USB | NEC Controller: - 4 x USB 3.0/2.0 ports (2 ports at mid-board, 2 ports at back panel) Chipset built-in: - 8 x USB 2.0/1.1 ports (4 ports at mid-board, 4 ports at back panel) ASUS CrashFree BIOS 3 AI Suite II TurboKey II |
| ASUS Unique Features | Mem OK! Q-FAN Anti-surge DTS Surround Sensation UltraPC ASUS@Vibe Support 1 x PS/2 Keyboard/Mouse Combo port 1 x DVI 1 x HDMI 1.3b 1 x External SATA 6Gb/s 1 x LAN(RJ45) port(s) 2 x USB 3.0/2.0 4 x USB 2.0/1.1 1 x S/PDIF Out (optical) 1 x Bluetooth 3.0 adapter 2 x Wifi antenna ports 3 x Audio jacks 1 x USB 3.0/2.0 connector(s) support additional 2 USB 3.0 ports 2 x USB 2.0/1.1 connector(s) support additional 4 USB 2.0 ports 1 x MemOK! switch 5 x SATA 6.0Gb/s connectors 1 x CPU Fan connector(s) 1 x Chassis Fan connector(s) 1 x Chassis Intrusion connector 1 x S/PDIF Out connector 1 x 4-pin ATX 12V Power connector 1 x 24-pin EATX Power connector 1 x Front panel audio connector 1 x System Panel connector 1 x Turbo Key II switch |
| Back Panel I/O Ports | 1 x USB 3.0/2.0 connector(s) support additional 2 USB 3.0 ports 2 x USB 2.0/1.1 connector(s) support additional 4 USB 2.0 ports 1 x MemOK! switch 5 x SATA 6.0Gb/s connectors 1 x CPU Fan connector(s) 1 x Chassis Fan connector(s) 1 x Chassis Intrusion connector 1 x S/PDIF Out connector 1 x 4-pin ATX 12V Power connector 1 x 24-pin EATX Power connector 1 x Front panel audio connector 1 x System Panel connector 1 x Turbo Key II switch |
| Internal I/O Connectors | 1 x USB 3.0/2.0 connector(s) support additional 2 USB 3.0 ports 2 x USB 2.0/1.1 connector(s) support additional 4 USB 2.0 ports 1 x MemOK! switch 5 x SATA 6.0Gb/s connectors 1 x CPU Fan connector(s) 1 x Chassis Fan connector(s) 1 x Chassis Intrusion connector 1 x S/PDIF Out connector 1 x 4-pin ATX 12V Power connector 1 x 24-pin EATX Power connector 1 x Front panel audio connector 1 x System Panel connector 1 x Turbo Key II switch |
| BIOS | 32 Mb Flash ROM , AMI BIOS, PnP, DMI 2.0, WfM 2.0, ACPI 2.0a, SM BIOS 2.6 User's manual 1 x I/O Shield |
| Accessories | 2 x SATA 6.0Gb/s cables 2 x Wifi antennas 1 x Support DVD |
| Support Disc | Drivers Anti-virus software (OEM version) ASUS Update |

ASUS Utilities
Form Factor Mini ITX Form Factor
6.7 inch x 6.7 inch (17 cm x 17 cm)