



AX18XX-B 15W - 18W Series Switching Power Adapter

PICTURES	SPECIFICATIONS
	<p>Input Characteristics</p> <p>Voltage 100 ~ 240Vac Frequency 50 to 60Hz Inrush Current 30A Max. @ 115Vac Conducted EMI CISPR22 class B Safety UL60950 Leakage Current 0.25mA Max.</p> <p>Output Characteristics</p> <p>Hold-up Time 10mS . @ 115Vac Short Circuit Protection Continuous Over Voltage Protection Option</p> <p>Environmental Characteristics</p> <p>Operating Temperature 0 ~ 40°C Storage Temperature -25 ~ +85°C</p> <p>Mechanical Characteristics</p> <p>Dimensions 74 x 47 x 34 m/m Weight 123.2 g AC Plug US 2 PIN</p>
	<p>  Powered by an ENERGY STAR® qualified adaptor for a better environment</p>



Model	O/P Voltage	O/P Current	Ripple & Noise	Line Regulation	Load Regulation
AF1805-B	5V	0~3.00A	50mV	+/-1%	+/-5%
AF1806-B	6V	0~2.50A	60mV	+/-1%	+/-5%
AF1807-B	7V	0~2.14 A	70mV	+/-1%	+/-5%
AF1808-B	8V	0~1.87 A	80mV	+/-1%	+/-5%
AG1809-B	9V	0~2.00A	90mV	+/-1%	+/-5%
AG1810-B	10V	0~1.80 A	100mV	+/-1%	+/-5%
AG1811-B	11V	0~1.63 A	110mV	+/-1%	+/-5%
AH1812-B	12V	0~1.50A	120mV	+/-1%	+/-5%
AH1813-B	13V	0~1.38A	130mV	+/-1%	+/-5%
AH1814-B	14V	0~1.28A	140mV	+/-1%	+/-5%
AH1815-B	15V	0~1.20A	150mV	+/-1%	+/-5%

JENTEC TECHNOLOGY CO., LTD.

17F-10, No.2, Jian-Ba Rd .Chung-Ho City , Taipei Hsien , Taiwan , R.O.C

TEL: (886)2-8226-2057 FAX:(886)2-8226-2077

E-mail:allen@jentec.com.tw Web: www.jentec.com.tw



AX18XX-E 15W - 18W Series Switching Power Adapter

PICTURES	SPECIFICATIONS
 	<p>Input Characteristics</p> <p>Voltage 100 ~ 240Vac Frequency 50 to 60Hz Inrush Current 30A Max. @ 115Vac Conducted EMI CISPR22 class B Safety EN60950 Leakage Current 0.25mA Max.</p> <p>Output Characteristics</p> <p>Hold-up Time 10mS . @ 115Vac Short Circuit Protection Continuous Over Voltage Protection Option</p> <p>Environmental Characteristics</p> <p>Operating Temperature 0 ~ 40°C Storage Temperature -25 ~ +85°C</p> <p>Mechanical Characteristics</p> <p>Dimensions 75 x 47 x 34 m/m Weight 129.2g AC Plug EU 2 PIN</p> <div style="text-align: right;">   <p>Powered by an ENERGY STAR® qualified adaptor for a better environment</p> </div>



Model	O/P Voltage	O/P Current	Ripple & Noise	Line Regulation	Load Regulation
AF1805-E	5V	0~3.00A	50mV	+/-1%	+/-5%
AF1806-E	6V	0~2.50A	60mV	+/-1%	+/-5%
AF1807-E	7V	0~2.14 A	70mV	+/-1%	+/-5%
AF1808-E	8V	0~1.87 A	80mV	+/-1%	+/-5%
AG1809-E	9V	0~2.00A	90mV	+/-1%	+/-5%
AG1810-E	10V	0~1.80 A	100mV	+/-1%	+/-5%
AG1811-E	11V	0~1.63 A	110mV	+/-1%	+/-5%
AH1812-E	12V	0~1.50A	120mV	+/-1%	+/-5%
AH1813-E	13V	0~1.38A	130mV	+/-1%	+/-5%
AH1814-E	14V	0~1.28A	140mV	+/-1%	+/-5%
AH1815-E	15V	0~1.20A	150mV	+/-1%	+/-5%

JENTEC TECHNOLOGY CO., LTD.