

ZONE	REV.	DESCRIPTION	DRAWN	DATE
	A0	初版发行		



CONNECTION DETAIL

CN1	COLOR	CONN
1	NC 空(堵孔)	
2	Black 黑色	CN2-2
3	Red 红色	CN2-1
4	White 白色	TER

加工说明:

- 1.开线长度: 314mm(红x1, 黑x1); 316mm(白色);
- 2.CN1端: 剥线口2.5mm打端子, PIN1孔堵孔;
- 3.CN2端: 剥线口3.8mm打端子
- 4.CN3端: 剥线口8.0mm上锡打端子
- 5.端子拉力按UL486标准执行。

Note/备注:

1. Electrical function/电性功能
 - a. 100% open & short testing/100%开路&短路测试;
 - b. Conductive resistance/导通阻抗: 2 Ohm(Max);
 - c. Insulation resistance/绝缘电阻: DC 300V 10M Ohm(Min);
 - d. Withstanding voltage /耐电压: AC 200V 0.01Sec;
2. There is no bad appearance/无外观不良。

7	10410072603	WIRE	UL1007 26AWG(7/0.16TS) OD=1.3MM WHITE白色	316	MM	
	10410072613		UL1007 26AWG(7/0.16TS) OD=1.3MM BLACK黑色	314	MM	
	10410072610		UL1007 26AWG(7/0.16TS) OD=1.3MM RED红色	314	MM	
6		TER	MF1-6.4AF 端子带粉红色绝缘护套(上億)	1	PCS	
5		HSG	杜邦2.54-1x2Pin	1	PCS	
4		TER	杜邦2.54-T-母端子 镀锡	2	PCS	
3		HSG	杜邦2.0-2x2Pin	1	PCS	
2		STOPPER	杜邦2.0黑色塞子	1	PCS	
1		TER	杜邦2.0-T 母端子 镀半金	3	PCS	
No.	Mat'l P/N	Item	Material	Q'ty	Unit	Remark

Material Description

Third Angle 3RD:		ZHENJINAG E-TECH ELECTRONICS CO., LTD.		
Scale:N/A		Customer	MB	Product P/N.
Tolerances Unless Otherwise Specified		03-16136 REV.A0		
Length	Product Name			
	Customer P/N.		CBL-M3-ATX-thump 300mm	
	Project&Drawing			
Size	Quote&Sample			
	Unit:mm	Size:A4	Page:1/1	
	Drawn	Checked	Approval	
Rong 2017.05.20				